



NIPPON QUALITY-PRIMER / WALL PRIMER (For Interior)

Recommended Uses

For use in interior, plastered walls, ceilings, brickwork, hard and soft board.

Composition

Pigments : Titanium Dioxide and Mineral Extender
Binder : Acrylic Emulsion
Thinner : Water

Application Methods:

Thinning by volume

- 1) **Brush** : 50-60% with water
- 2) **Roller** : 20-30% with water
- 3) **Air Spray** : 30-40% with water

Product Description

Nippon Quality-Primer Wall Sealer is an acrylic water based wall sealer. It is specially formulated for interior walls to prime the surface and protect finishing coats against the effects of mild alkalinity and moisture from the substrate.



Surface Preparation

BARED SURFACE

Remove all loose, defective paint or powdery residues. Repair cracks, uneven surfaces with Nippon Putty or suitable fillers. Smoothen the putty / filler areas with sandpaper. Surfaces to be painted must be cleaned thoroughly and dry, it must be free from dirt, grease and other foreign matters. Allow all surfaces to dry completely prior to painting. Avoid painting when the moisture content and alkalinity of the walls are still high. (Recommended painting specification requires the moisture content of the walls to be below 16% measured by porosimeter and alkalinity of the walls to be below pH9.)

Previously Painted Surfaces

Remove all unstable paint film, loose chalk, dust and foreign matter. Spot prime with NIPPON QUALITY-PRIMER WALL SEALER to clean off any surface defects.



Recommended Paint System

Type of Substrate:
MASONRY SURFACE

Sequence	Product Name	No. of Coats	Remarks
Sealer	NIPPON QUALITY-PRIMER / WALL SEALER	1	
Finish	NIPPON QUALITY EMULSION / NIPPON EASYCOAT EMULSION / NIPPON MATEX GOLD	3	

Standard Packing : 0.91 Lit,; 3.64 litres, 14.56 litres

Safety, Health and Environmental Information

- Keep container tightly closed and keep it out of reach of children or away from food and drinks
- Ensure good ventilation during application and drying.
- When applying paint, it is advisable to wear eye protection.
- In case of contact with eye, rinse with plenty of water immediately and seek medical advice. Remove splashes from skin by using soap or water.
- Paint must always be stored in a cool and dry place.
- When transporting paint, care must be taken. Always keep container in a secure upright position.
- Dispose off any paint waste in accordance with the appropriate Environmental Quality Regulations