

Dulux Interior Acrylic Putty



Product Code	F94X-6661
Usage	Dulux Interior Acrylic Putty (water based) is an economical, ready-to-use filler that has excellent whiteness, coverage, and application properties. Its high-quality filling properties has made it ideal for use on all types of interior masonry surfaces. It provides a smooth base for topcoat application of all Decorative products. Dulux Interior Acrylic Putty is not recommended for exterior use.
Pack Size	20 Kg
Colour Range	White only
FILM PROPERTIES	
Water resistance	Will tolerate the levels of atmospheric humidity present in normal interior environment
Other Properties	Low Odour and Low VOC, No Added Lead or Mercury, Singapore Green Label Certified
COMPOSITION (NOMINAL)	Pigment: Non-Lead Pigments. Binder: Acrylic Copolymer Emulsion. Solvent: Water
VOLUME SOLIDS	48% (nominal)
FILM THICKNESS/ LITRE/COAT	Wet: 150-200 micrometers. Dry: 80-100 micrometers.
Touch Dry Recoat	Single coat at standard film thickness. Dependent on temperature and humidity 2-3 hours.
PRACTICAL COVERAGE	A guide to the practical coverage which can be achieved under normal conditions is 4-6 m ² /Kg/coat.
CLEANING UP	Clean all equipment with clean water immediately after use.

SURFACE PREPARATION New surfaces must be clean, dry, free from all defective or poorly adhering material, dirt, grease, wax etc. Treat any area affected by mould, lichens, algae or moss with Aquashield Pre Treatment Coat. Previously painted surfaces should be thoroughly rubbed down using a suitable abrasive paper and then dust off.

FILLING NEW SURFACES After priming new surfaces with Dulux Prime On / Interior Acrylic Primer, fill the surface with Dulux Interior Acrylic Putty - water based. Allow the filler to dry for 2-3 hours and apply second coat of Putty. Third coat is recommended for extra smoothness. For best results apply one coat of prime-on / Interior Acrylic Primer again over Interior Acrylic putty and dry overnight.

SYSTEM INFORMATION

New Surfaces

Dulux Prime-On (500-368) / Interior Acrylic Primer (F919-002) – 1 Coat Primer
Dulux Interior Acrylic Putty (2-3 Coats)
Dulux Prime-On (500-368) / Interior Acrylic Primer (F919-002) – 1 Coat Primer

Finish

Powdery Surfaces

Dulux Prime-On (500-368) / Interior Acrylic Primer (F919-002)
(Int. Acrylic Putty 2 coats if required)

Interior Emulsions
(3-4 coats)

Or

Matt Enamel (2-3 coats)

Normal, Sound Surfaces
(previously painted)

No Primer required

SAFETY, HEALTH AND ENVIRONMENT INFORMATION

Treatments such as sanding, burning off etc. of paint films may generate hazardous dust and/or fumes. Wet sanding/ flatting should be used wherever possible. Work in well ventilated areas. Use suitable personal protection equipment.



Lift with care – gross weight exceeds 10kg

Wear eye/ hand protection. Do not breathe vapors/spray. Use only in well-ventilated areas. Remove as much paints as possible from brushes and rollers before cleaning. Avoid release to the environment. Collect spillage. Keep away from food, drinks and animal feed. Store in a cool and shaded place. Container must be in a secure, upright position and be tightly closed. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. In case of contact with skin wash immediately with soap and water or a proprietary skin cleanser. Do not use solvents or thinners. Do not empty into water course. Safety data sheet available for professional/ user on request.



WARNING

Hazard Statements

May cause an allergic skin reaction. Toxic to aquatic life with long lasting effects.

Precautionary Statements

Keep out of reach of children. If medical advice is needed, have product container or label at hand. Do not get in eyes, on skin, or on clothing. Call a POISON CENTER or doctor if you feel unwell. Dispose of contents and container in accordance with all local, regional, national or international regulations.