

## Dulux Water Repellent



**Product code**

F285-2296

**Usage**

Dulux Water Repellent is an excellent protective barrier against moisture for unpainted surfaces. It penetrates the surface and act as an effective guard against water. It is suitable for brickwork, concrete, plastered surfaces, unglazed tiles and sand-cast surfaces. Dulux Water Repellent is not recommended for surfaces in constant contact with water, like water tanks or masonry surfaces below ground level like basement etc.

**Pack Size**

3.64 Litres and 200 Litres.

**Colour Range**

Clear

**Other Properties**

The Invisible Moisture Guard, No Added Lead or Mercury

**COMPOSITION (NOMINAL)**

Pigment: N/A  
Binder: Silicon  
Solvent: Mineral turpentine.

**DRYING TIMES**

Single coat at standard film thickness

**Touch Dry**

30 minutes.

**Recoat**

16 hours.

**PRACTICAL COVERAGE**

A guide to the practical coverage which can be achieved under normal conditions is 4-6m<sup>2</sup> /litre /coat.

**APPLICATION**

Brush



Spray



**THINNING**

**Brush Application**

Ready to use. Apply generously in short strokes

**Spray**

Ready to use. It is recommended that lowest possible pressure be used in order to avoid excessive atomization and achieve maximum wetting.

## SPRAY RECOMMENDATIONS

**Conventional Spray** Satisfactory through most equipment

**CLEANING UP** Clean all equipment with Mineral turpentine immediately after use

**SURFACE PREPARATION** Surface generally must be clean, dry, free from all defective or poorly adhering material, dirt, and grease, wax etc. previously painted surfaces should be thoroughly rubbed down using a suitable abrasive paper and then dusted off. If mould is present, treat with Aquashield Pre Treatment Coat. Allow this to stand on the masonry surface for at least 4 hours before rinsing with clean water. Allow the surface to dry; application to fresh plaster which still contains a high-water content limits the effectiveness of this process. Apply by brush or spray a generous coat of Weathershield water repellent. When spraying, the lowest possible pressure should be used to avoid excessive atomization and to achieve maximum wetting.

## SYSTEM INFORMATION

Primer No primer required	Finish (2 coats) Dulux Water Repellent (F285-2296)
---------------------------------	--

## FLASH POINT

32<sup>0</sup>

## NOTE

If rain falls within 24hrs of application, it will reduce the efficiency of the product. Allow surface to dry completely and apply an extra coat.

## SAFETY, HEALTH AND ENVIRONMENT INFORMATION

**Flammable.** In case of fire use foam, dry powder, AFFF, CO<sub>2</sub> fire extinguisher. Never use water. No smoking. Keep out of reach of children. Keep away from sources of ignition. Keep container tightly closed and upright to prevent leakage when not in use. Work only in areas of good ventilation. Inside, always keep doors and windows fully open during application and drying. Irritating to eyes and skin and may produce an allergic reaction. When applying paint it is advisable to wear eye protection. In case of contact with eyes rinse immediately with plenty of water keeping eyelids apart and seek medical advice. Repeated exposure may cause skin dryness or cracking. Wear gloves while working. In case of contact with skin use soap and water or a recognized skin cleaner. Use suitable respiratory equipment while applying paint in narrow spaces. Dry sanding, flame cutting and or welding of the dry paint film will give rise to dust and or hazardous fumes. Wet sanding should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used. In case of insufficient ventilation during spraying wear suitable respiratory equipment, a suitable cartridge mask should be worn provided the filter is changed regularly. All respiratory equipment must meet an appropriate approved standard. Do not breathe vapor or sanding dust. If inhalation causes physical discomfort, move to fresh air. If discomfort persists or any breathing difficulty occurs, move to fresh air and seek medical advice by showing container label. Harmful if swallowed seek medical advice immediately. Care must be taken when transporting paint. Keep container tightly closed and upright to prevent leakage when not in use. Store in a cool and dry place. In the event of an accident, collect spillage using sand or earth. Do not empty into drains or watercourses. Very toxic to aquatic organisms. May cause long term adverse effects in the aquatic environment. Dispose of any paint waste in accordance with the appropriate environment quality regulations. Safety Data Sheet available for professional users on request. This container is only for paint use.

**CONTAINS NO ADDED LEAD OR MERCURY**