

Dulux Woodcare Special Thinner



PRODUCT CODE F851-4444

Usage Dulux Woodcare Special Thinner has the quality and strength to make all Woodcare products to be soluble to their maximum. It makes all Woodcare product applications easier. It cleans the equipment efficiently, making the most of wood's natural qualities. It produces finishes that are easy to apply and easy to maintain allowing the inherent character and style of the material to shine through.

Pack Size 0.91 Litre and 3.64 Litres

Colour Range Clear White

FILM PROPERTIES

Flammability Highly flammable

Water Resistance Withstand to the levels of atmospheric humidity
normal interior and exterior environments

Other Properties No Added Lead or Mercury

COMPOSITION Mixture of solvents

FLASH POINT 12C°

THINNING RATIO Sealer: 1:1-1.5 Thinning with Woodcare Special Thinner
Lacquer: 1:1-1.5 Thinning with Woodcare Special Thinner

CLEANING UP Clean all equipment with Woodcare Special Thinner immediately after use.

OPTIMAL WORKING CONDITIONS Good Ventilation

SAFETY, HEALTH AND ENVIRONMENT INFORMATION

Highly flammable. Harmful by inhalation & in contact with skin. Keep out of reach of children. Do not breath solvent Vapor/spray. Keep container in a well-ventilated place. Irritating to eyes, respiratory system & skin. Keep away from food, drink & animal feeding stuff. **Contains Aromatic & Aliphatic solvents.** Wear suitable protective clothing & gloves. Avoid contact with eyes and skin. In case of contact with eyes rinse immediately with plenty of water and seek medical advice. Keep away from sources of ignition. No smoking. Take precautionary measures against static discharges. Wear suitable protective equipment during sanding. Dry sanding of the dry paint film will give rise to paint and wooden dust, such type of surfaces should be sanded with wet sanding paper. If swallowed, rinse mouth with water (only if the person is conscious) & show this container or label to a medical practitioner. In case of fire use foam, dry powder, AFFF, CO₂ never use water. Is very toxic to aquatic organisms and may cause long term adverse effects in the aquatic environment. Do not empty into drains. Dispose of any paint in accordance with the appropriate Environment Regulations. This container is only for paint use. Safety Data Sheet available for professional users on request.