

## Dulux Ambiance VT Diamond Glo



<b>Product Code</b>	F901
<b>Usage</b>	Dulux Ambiance VT Diamond Glo is acrylic based premium quality paint. It is an ultra-luxurious water based interior emulsion with the smooth touch of velvet. Dulux Ambiance Velvet Touch is recommended for interior surfaces only.
<b>Pack Size</b>	1 Litres and 4 Litres
<b>Colour Range</b>	See Dulux Ambiance Shade card
<b>FILM PROPERTIES</b>	
<b>Water resistance</b>	Will tolerate the levels of atmospheric humidity present in normal interior environment
<b>Other Properties</b>	Colour Guard, High Coverage and Strong Hiding Power, Smooth Finish, Low Odour and Low VOC, No Added Lead or Mercury, Singapore Green Label Certified
<b>COMPOSITION (NOMINAL)</b>	Pigment: Lightfast Non-Lead Pigments Binder: Acrylic copolymer Solvent: Water
<b>VOLUME SOLIDS</b>	White 36% (nominal), other colours will vary.
<b>FILM THICKNESS/ LITRE/COAT</b>	Wet: 60-70 micrometers Dry: 25-30 micrometers
<b>DRYING TIMES</b>	Single coat at standard film thickness
<b>Touch Dry</b>	Dependent on temperature and humidity
<b>Recoat</b>	2-3 hours
<b>PRACTICAL COVERAGE</b>	A guide to the practical coverage which can be achieved under normal conditions is 16-18m <sup>2</sup> /litre /coat.

## APPLICATION



## THINNING

### Brush

For sealing new or bare surfaces thin with up to 3 parts of clean water to 4 parts of paint (75%). For application with brush thinning should not exceed 2-3 parts of clean water to 4 parts of paint (60-70%).

### Roller

For application with roller thinning should not exceed 0.5-0.75 parts of clean water to 4 parts of paint (10-15%).

## CLEANING UP

Clean all equipment with clean water immediately after use.

## SURFACE PREPARATION

New surfaces must be clean, dry, free from all defective or poorly adhering material, dirt, grease, wax etc. Treat any area affected by mould, lichens, algae or moss with Aquashield Pre Treatment Coat. Previously painted surfaces should be thoroughly rubbed down using a suitable abrasive paper and then dust off.

## FILLING NEW SURFACES

After priming new surfaces with Dulux Int. Acrylic Primer or Dulux Prime on fill the surface with Int. Acrylic Putty. Please refer to PDS of Int. Acrylic Putty for correct application procedure and drying time properties. Third coat of Int. Acrylic Putty can be applied for extra smoothness. For best results apply one coat of Int. acrylic Primer again over wall putty and dry 3-4 hours.

## POWDRY SURFACES

Make good minor defects. For larger holes and cracks use sand and cement mixture. Allow the surface to dry completely. Prime surface with Dulux Int. Acrylic Primer or Dulux Prime on and then fill any surface imperfections with the Int. Acrylic Putty. Scuff surface using abrasive paper and dust off.

## SYSTEM INFORMATION

### New Surface

Dulux Interior Acrylic Primer (F919-0002) /  
Dulux prime-on (F500-368) – 1 coat Primer  
Dulux Int. Acrylic Putty (F94X-6661) 2 Coat  
for best results apply third coat  
Dulux Interior Acrylic Primer (F919-0002) /  
Dulux prime-on (F500-368),

Finish (3-4  
coats)

### Powdery surfaces

Dulux Interior Acrylic Primer (F919-0002) /  
Dulux prime-on (F500-0368) – 1 coat Primer  
(Int. Acrylic Putty 2 coats if required)

Dulux Ambiance  
VT Diamond Glo  
(F901)

### Normal, sound surfaces (Previously painted)

No primer required

## SAFETY, HEALTH AND ENVIRONMENT INFORMATION

Treatments such as sanding, burning off etc. of paint films may generate hazardous dust and/or fumes. Wet sanding/ flatting should be used wherever possible. Work in well ventilated areas. Use suitable personal protection equipment.



Lift with care – gross weight exceeds 10kg

Wear eye/ hand protection. Do not breathe vapors/spray. Use only in well-ventilated areas. Remove as much paints as possible from brushes and rollers before cleaning. Avoid release to the environment. Collect spillage. Keep away from food, drinks and animal feed. Store in a cool and shaded place. Container must be in a secure, upright position and be tightly closed. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. In case of contact with skin wash immediately with soap and water or a proprietary skin cleanser. Do not use solvents or thinners. Do not empty into water course. Safety data sheet available for professional/ user on request.



### WARNING

#### Hazard Statements

May cause an allergic skin reaction.

#### Precautionary Statements

Keep out of reach of children. If medical advice is needed, have product container or label at hand. Do not get in eyes, on skin, or on clothing. Call a POISON CENTER or doctor if you feel unwell. Dispose of contents and container in accordance with all local, regional, national or international regulations.