

Dulux Aquashield Pre Treatment Coat



USAGE

Dulux Aquashield Pre Treatment Coat is a high-performance surface preparation product with Fungi Clean technology that provides protection against fungal attacks. Its unique Anti-Microbial Pack generates chemicals against fungal and algal growth developing on the surface.

Other Properties

Low Odor and Low VOC, No Added Lead or Mercury

PACK SIZE

1 L

COLOUR RANGE

No color

Composition (Nominal)

Binder: Acrylic Co-Polymer Latex
Solvent: Water

DRYING TIMES

Single coat at standard thickness

Touch Dry

Dependent on temperature and humidity


Recoat

4-6 hours, depends on weather condition.

PRACTICAL COVERAGE:

Varies considerably according to the roughness and porosity of the surface. On smooth surfaces of average porosity, practical coverage 110-112 m²/Liter/coat.

APPLICATION:

Brush 

THINNING

10-12 L water in 1L Product

CLEANING UP

Clean all equipment with clean water immediately after use

SURFACE PREPARATION & APPLICATION:

Remove any fungal, algal, lichen or moss growth by scrapping with wire brush. Clean the surface thoroughly for any powdery loose particles by brushing and water jetting. Allow the surface to dry completely. For best performance, all existing coatings where old fungal/algal growth may have been trapped, should be scrapped. It is recommended to add 10-12 liters of water in

one liter of this product. Apply one coat of diluted Dulux Aquashield Pre-treatment Coat and allow to dry for 4-6 hours.

Note: Do not apply Dulux Aquashield Pre-Treatment Coat during wet weather.

SAFETY, HEALTH AND ENVIRONMENT INFORMATION

Treatments such as sanding, burning off etc. of paint films may generate hazardous dust and/or fumes. Wet sanding/ flatting should be used wherever possible. Work in well ventilated



areas. Use suitable personal protection equipment.

Lift with care – gross weight exceeds 10kg

Wear eye/ hand protection. Do not breathe vapors/spray. Use only in well-ventilated areas. Remove as much paints as possible from brushes and rollers before cleaning. Avoid release to the environment. Collect spillage. Keep away from food, drinks and animal feed. Store in a cool and shaded place. Container must be in a secure, upright position and be tightly closed. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. In case of contact with skin wash immediately with soap and water or a proprietary skin cleanser. Do not use solvents or thinners. Do not empty into water course. Safety data sheet available for professional/ user on request.



WARNING

Hazard Statements


May cause an allergic skin reaction. Toxic to aquatic life with long lasting effects.

Precautionary Statements

Keep out of reach of children. If medical advice is needed, have product container or label at hand. Do not get in eyes, on skin, or on clothing. Call a POISON CENTER or doctor if you feel unwell. Dispose of contents and container in accordance with all local, regional, national or international regulations.

Dulux Aquashield Interior Waterproof Basecoat



USAGE	Dulux Aquashield Interior Waterproof Basecoat is a high-quality premium basecoat that provides waterproof protection to interior walls. Its revolutionary DampProtect Technology guards interior walls against dampness, enhances top coat life and prevents alkali salt deposits.
Other Properties	Crack proof, Enhances top coat life, Low Odor and Low VOC, No Added Lead or Mercury, Singapore Green Label Certified
PACK SIZE	1 L, 4 L, 16 L
COLOUR RANGE	White
Composition (Nominal)	Pigment: Lightfast Non-Lead/Chrome Pigments Binder: Acrylic Co-Polymer Binder Solvent: Water
VOLUME SOLIDS	White 41% (nominal)
DRYING TIMES	Single coat at standard thickness
Touch Dry	Dependent on temperature and humidity
Recoat	3-4 hours, depends on weather condition.
FILM THICKNESS /LITRE/COAT	DFT: 50-60 micrometers
PRACTICAL COVERAGE:	Varies considerably according to the roughness and porosity of the surface. On smooth surfaces of average porosity, practical coverage 7-9m ² /Liter/coat.
APPLICATION	Brush 
THINNING CLEANING UP	No dilution required Clean all equipment with clean water immediately after use

SURFACE PREPARATION Allow all new surfaces to dry out completely. Remove all loose or defective paint or powdery residues by thorough brushing or scraping using a stiff fiber brush. Treat any areas affected by mould, lichens, algae and moss with Dulux Aquashield Pre-Treatment Coat.

Repair minor and major defects in the wall using sand and cement mixture. Allow the surface drying time and prepare the surface as described above

Note: Do not apply Dulux Aquashield Interior Waterproof Basecoat during wet weather.

SYSTEM INFORMATION

New Surface

Dulux Aquashield Waterproofing Interior Basecoat 1 coat, 2-3 coats of Dulux Acrylic Interior Putty, 1 coat of Dulux Acrylic Interior Primer

Powdery surfaces

Dulux Aquashield Waterproofing Interior Basecoat 1 coat, 2-3 coats of Dulux Acrylic Interior Putty, 1 coat of Dulux Acrylic Interior Primer

Normal, sound surfaces
(Previously painted)

Dulux Aquashield Waterproofing Interior Basecoat 1 coat, 2-3 coats of Dulux Acrylic Interior Putty, 1 coat of Dulux Acrylic Interior Primer

Finish: 3-4 coats of any interior Dulux topcoat

SAFETY, HEALTH AND ENVIRONMENT INFORMATION

Treatments such as sanding, burning off etc. of paint films may generate hazardous dust and/or fumes. Wet sanding/ flatting should be used wherever possible. Work in well ventilated



areas. Use suitable personal protection equipment.

Lift with care – gross weight exceeds 10kg

Wear eye/ hand protection. Do not breathe vapors/spray. Use only in well-ventilated areas. Remove as much paints as possible from brushes and rollers before cleaning. Avoid release to the environment. Collect spillage. Keep away from food, drinks and animal feed. Store in a cool and shaded place. Container must be in a secure, upright position and be tightly closed. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. In case of contact with skin wash immediately with soap and water or a proprietary skin cleanser. Do not use solvents or thinners. Do not empty into water course. Safety data sheet available for professional/ user on request.



WARNING

Hazard Statements

May cause an allergic skin reaction. Toxic to aquatic life with long lasting effects.

Precautionary Statements

Keep out of reach of children. If medical advice is needed, have product container or label at hand. Do not get in eyes, on skin, or on clothing. Call a POISON CENTER or doctor if you feel unwell. Dispose of contents and container in accordance with all local, regional, national or international regulations.