

Dulux Interior Acrylic Primer



Product code	F919-0002
Usage	Dulux Interior Acrylic Primer is a 100% acrylic based primer suitable for all types of interior masonry surfaces. It has excellent adhesion to most of interior substrates e.g. masonry surface, brickwork, wallboard etc. It also provides alkali resistance resulting in extra durability for topcoat.
Pack Size	1 Litre, 4 Litres and 16 Litres
Colour	White
FILM PROPERTIES	
Water resistance	Will tolerate the levels of atmospheric humidity present in normal interior environments
Other Properties	Low Odour and Low VOC, No Added Lead or Mercury, Singapore Green Label Certified
COMPOSITION (NOMINAL)	Pigment: Lightfast Non-Lead Pigments Binder: Acrylic copolymer Solvent: Water
VOLUME SOLIDS	White 43% (nominal), other colours will vary.
FILM THICKNESS/ LITRE/COAT	Wet: 60-70 micrometers Dry: 25-30 micrometers
DRYING TIMES	Single coat at standard film thickness
Touch Dry	Dependent on temperature and humidity
Recoat	2-3 hours
PRACTICAL COVERAGE	A guide to the practical coverage which can be achieved under normal conditions is 16-18m ² /litre /coat.

APPLICATION



THINNING

Brush

For sealing new or bare surfaces, thin with up to 2-3 parts of clean water to 4 parts of paint (50%-75%).

Roller

For application with roller, thinning should not exceed 0.8-1 parts of clean water to 4 parts of paint (20-25%)

CLEANING UP

Clean all equipment with clean water immediately after use

SURFACE PREPARATION

New surfaces must be clean, dry, free from all defective or poorly adhering material, dirt, grease, wax etc. Treat any area affected by mould, lichens, algae or moss with Aquashield Pre Treatment Coat. Previously painted surfaces should be thoroughly rubbed down using a suitable abrasive paper and then dust off.

FILLING NEW SURFACES

After priming new surfaces with Dulux Interior Acrylic Primer, fill the surface with Dulux Interior Acrylic Putty. Please refer to PDS of Dulux Interior Acrylic Putty for correct application procedure and drying time properties. For best results apply one coat of primer again over wall putty.

POWDRY, DUSTY SURFACES DEFECTS, CRACKS, AND OTHER SURFACES

Repair minor defects in the wall using sand whereas for larger holes and cracks use cement mix. Allow the surface drying time . Prime surface with Dulux Interior Acrylic Primer on scuffed surfaces using abrasive paper and dust off and then fill any surface imperfections with the Dulux Interior Acrylic Putty.

SYSTEM INFORMATION

New Surface

-Dulux Int. Acrylic Primer (F919-0002) 1 Coat
Dulux Interior Acrylic Putty (F94X-6661) 2-3 Coats, Dulux Int. Acrylic Primer (F919-0002) 1 Coat

Finish (3-4 coats)

Dulux Interior Emulsions

Powdery surfaces

-Dulux Int. Acrylic Primer (F919-0002) 1 Coat
(Int. Acrylic Putty 2 coats if required)

Normal, sound surfaces (previously painted)

1 coat of Dulux Int. Acrylic Primer (F919-0002) -Optional, however primer application will improve topcoat performance.

SAFETY, HEALTH AND ENVIRONMENT INFORMATION

Treatments such as sanding, burning off etc. of paint films may generate hazardous dust and/or fumes. Wet sanding/ flatting should be used wherever possible. Work in well ventilated areas. Use suitable personal protection equipment.



Lift with care – gross weight exceeds 10kg

Wear eye/ hand protection. Do not breathe vapors/spray. Use only in well-ventilated areas. Remove as much paint as possible from brushes and rollers before cleaning. Avoid release to the environment. Collect spillage. Keep away from food, drinks and animal feed. Store in a cool and shaded place. Container must be in a secure, upright position and be tightly closed. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. In case of contact with skin, wash immediately with soap and water or a proprietary skin cleanser. Do not use solvents or thinners. Do not empty into water course. Safety data sheet available for professional/ user on request.



WARNING

Hazard Statements

May cause an allergic skin reaction.

Precautionary Statements

Keep out of reach of children. If medical advice is needed, have product container or label at hand. Do not get in eyes, on skin, or on clothing. Call a POISON CENTER or doctor if you feel unwell. Dispose of contents and container in accordance with all local, regional, national or international regulations.