

## Dulux Prime-On



<b>Product code</b>	F500-0368
<b>Usage</b>	Dulux Prime-On is a high quality solvent based sealer for masonry surfaces. It is ideal for use on all interior surfaces. It reduces damage from alkali and salts and seals powdery, porous surfaces.
<b>Pack Size</b>	0.91 Litre, 3.64 Litres and 14.56 Litres
<b>Colour Range</b>	White only
<b>FILM PROPERTIES</b>	
<b>Water resistance</b>	Not suitable where the surface is saturated
<b>Other Properties</b>	Excellent Sealing Properties, Improving Adhesion, Alkali Resistant, No Added Lead or Mercury. Pakistan Standards Certified.
<b>COMPOSITION (NOMINAL)</b>	Pigment: Lightfast Non Lead Pigments Binder: Alkyd Solvent: Mineral turpentine
<b>VOLUME SOLIDS</b>	50% (nominal)
<b>FILM THICKNESS/ LITRE/COAT</b>	Wet: 40-50 micrometres Dry: 20-25 micrometres
<b>DRYING TIMES</b>	Single coat at standard film thickness
<b>Touch Dry</b>	2-4 hours. Dependent on temperature and humidity
<b>Recoat</b>	16 hours
<b>PRACTICAL COVERAGE</b>	A guide to the practical coverage which can be achieved under normal conditions is 14-16m <sup>2</sup> /litre /coat.

## APPLICATION



## THINNING

### Brush or Roller

If required for sealing new or bare surfaces, thin up to 0.5-0.70 part of mineral turpentine to 4 parts of paint (10-20%)

### Spray

Add up to 1 parts of Mineral turpentine to 4 parts of paint (25%)

## SPRAY RECOMMENDATIONS

### Conventional Spray

Satisfactory through most equipment

## CLEANING UP

Clean all equipment with Mineral turpentine immediately after use

## SURFACE PREPARATION

Surface generally must be clean, dry, free from all defective or poorly adhering material, dirt, and grease, wax etc. Previously painted surfaces should be thoroughly rubbed down using a suitable abrasive paper and then dusted off

## FILLING NEW SURFACES

After priming new surface with Dulux Prime-On, fill any surface imperfections with Dulux Wall Putty. Allow the filler to dry before painting.

## POWDRY SURFACE

Cracks and other defects. Make good minor defects. For large holes and cracks, use sand and cement mixture. Allow to dry. Prime the surface with Dulux Prime-On, dry overnight and then fill any surface imperfections with Dulux Wall Putty as described above. Allow to dry for 3-4 hours. Scuff surface using abrasive paper and dust off.

## SYSTEM INFORMATION

### Masonry

Dulux Prime-On (F500-368)  
(2-3 coats of Dulux Wall Putty if required)

Finish (3-4 coats)

### Powdery surfaces

Primer (1 coat)  
Dulux Prime-On (F500-368)  
(2-3 coats of Dulux wall putty if required)

Dulux synthetic Enamel  
Or  
Dulux Matt Finish (Interior)  
Or  
Interior Emulsion

### Normal, sound surfaces (Previously painted)

No primer required

**FLASH POINT** 32°

## SAFETY, HEALTH AND ENVIRONMENT INFORMATION

**Flammable.** In case of fire use foam, dry powder, AFFF, CO<sub>2</sub> fire extinguisher. Never use water. No smoking. Keep out of reach of children. Keep away from sources of ignition. Keep container tightly closed and upright to prevent leakage when not in use. Work only in areas of good ventilation. Inside always keep doors and windows fully open during application and drying. Irritating to eyes and skin. Contains **COBALT CARBOXYLATE & METHYL ETHYL KETOXIME**. May produce an allergic reaction. When applying paint it is advisable to wear eye protection. In case of contact with eyes rinse immediately with plenty of water keeping eyelids apart and seek medical advice. Repeated exposure may cause skin dryness or cracking. Wear gloves while working. In case of contact with skin, use soap and water or a recognized skin cleaner. Use suitable respiratory equipment while applying paint in narrow spaces. Dry sanding, flame cutting and or welding of the dry paint film will give rise to dust and or hazardous fumes. Wet sanding should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used. In case of insufficient ventilation during spraying wear suitable respiratory equipment, a suitable cartridge mask should be worn provided the filter is changed regularly. All respiratory equipment must meet an appropriate approved standard. Do not breathe Vapor or sanding dust. If inhalation causes physical discomfort, move to fresh air. If discomfort persists or any breathing difficulty occurs, move to fresh air and seek medical advice by showing container label. Harmful if swallowed seek medical advice immediately. Care must be taken when transporting paint. Keep container tightly closed and upright to prevent leakage when not in use. Store in a cool and dry place. In the event of an accident, collect spillage using sand or earth. Do not empty into drains or watercourses. Very toxic to aquatic organisms. May cause long term adverse effects in the aquatic environment. Dispose of any paint waste in accordance with the appropriate environment quality regulations. Safety Data Sheet available for professional users on request. This container is only for paint use.

**CONTAINS NO ADDED LEAD OR MERCURY**