



Dulux Pentalite Classic



Product code	F935
Usage	Dulux Pentalite Classic is a 100% acrylic paint, suitable for all types of interior masonry surfaces. Based on the new ProCover+ Technology, Dulux Pentalite Classic, provides higher opacity and coverage as compared to ordinary paints. With the added benefits of ColourGuard Technology, Dulux Pentalite Classic also keeps your walls looking beautiful for longer.
Pack Size	1 Litres, 4 Litres and 16 Litres
Colour Range	See Dulux Pentalite Classic shade card
FILM PROPERTIES	
Water resistance	Will tolerate the levels of atmospheric humidity present in normal interior and exterior environments
Other Properties	Colour Guard, Smooth Finish, No Added Lead or Mercury, Low Odour and Low VOC, Singapore Green Label Certified
COMPOSITION (NOMINAL)	Pigment: Lightfast Non Lead Pigments Binder: Acrylic copolymer Solvent: Water
VOLUME SOLIDS	White 41% (nominal), other colours will vary.
FILM THICKNESS/ LITRE/COAT	Wet: 60-70 micrometers Dry: 25-30 micrometers
DRYING TIMES Touch Dry Recoat	Single coat at standard film thickness Dependent on temperature and humidity 2-3 hours
PRACTICAL COVERAGE	A guide to the practical coverage which can be achieved under normal conditions is 14-16m ² /litre /coat.
APPLICATION	Brush  Roller 

THINNING

Brush For sealing new or bare surfaces thin with up to 3 parts of clean water to 4 parts of paint (75%). For application with brush thinning should not exceed 2-3 parts of clean water to 4 parts of paint (60-70%).

Roller For application with roller thinning should not exceed 0.5-0.75 parts of clean water to 4 parts of paint (10-15%)

CLEANING UP Clean all equipment with clean water immediately after use

SURFACE PREPARATION New surfaces must be clean, dry, free from all defective or poorly adhering material, dirt, grease, wax etc. Treat any area affected by mould, lichens, algae or moss with Aquashield Pre Treatment Coat. Previously painted surfaces should be thoroughly rubbed down using a suitable abrasive paper and then dust off.

FILLING NEW SURFACES After priming new surfaces with Dulux Interior Acrylic Primer / Dulux Prime-on, fill the surface with Dulux Int. Acrylic Putty. Please refer to PDS of Int. Acrylic Putty for correct application procedure and drying time properties. Third coat of Int. Acrylic putty can be applied for extra smoothness. For best results apply one coat of primer again over wall putty and dry overnight.

POWDRY SURFACE Repair minor defects in the wall using sand whereas for holes, and cracks use cement mix. Allow the surface to dry. Prime surface with Dulux Int. Acrylic Primer or Dulux Prime on and then fill any surface imperfections with the Dulux Int. Acrylic Putty. Scuff surface using abrasive paper and dust off.

SYSTEM INFORMATION

New Surface	Dulux Interior Acrylic Primer (F919-0002) / Dulux prime-on (F500-368) – 1 coat Primer Dulux Int. Acrylic Putty (F94X-6661) 2 Coat for best results apply third coat Dulux Interior Acrylic Primer (F919-0002) / Dulux prime-on (F500-368),	Finish (3-4 coats)
Powdery surfaces	Dulux Interior Acrylic Primer (F919-0002) / Dulux prime-on (F500-0368) – 1 coat Primer (Int. Acrylic Putty 2 coats if required)	Dulux Pentalite Classic (acrylic based) (F935)
Normal, sound surfaces (Previously painted)	No primer required	

SAFETY, HEALTH AND ENVIRONMENT INFORMATION

Treatments such as sanding, burning off etc. of paint films may generate hazardous dust and/or fumes. Wet sanding/ flatting should be used wherever possible. Work in well ventilated areas. Use suitable personal protection equipment.



Lift with care – gross weight exceeds 10kg

Wear eye/ hand protection. Do not breathe vapors/spray. Use only in well-ventilated areas. Remove as much paints as possible from brushes and rollers before cleaning. Avoid release to the environment. Collect spillage. Keep away from food, drinks and animal feed. Store in a cool and shaded place. Container must be in a secure, upright position and be tightly closed. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. In case of contact with skin wash immediately with soap and water or a proprietary skin cleanser. Do not use solvents or thinners. Do not empty into water course. Safety data sheet available for professional/ user on request.



WARNING

Hazard Statements

May cause an allergic skin reaction.

Precautionary Statements

Keep out of reach of children. If medical advice is needed, have product container or label at hand. Do not get in eyes, on skin, or on clothing. Call a POISON CENTER or doctor if you feel unwell. Dispose of contents and container in accordance with all local, regional, national or international regulations.