

Dulux Synthetic Clear Varnish



Product code	F101-0118
Usage	Dulux Synthetic Clear Varnish is a solvent-based varnish suitable for use on all type of new or previously treated wood. Typical uses include paneling, cane or wood furniture, windows, door and partitions. Dulux Synthetic Clear Varnish has a high gloss finish and has excellent abrasion resistance and is fast drying.
Pack Size	0.75 Litre and 3 Litres.
Colour Range	Clear
Other Properties	No Added Lead or Mercury, Pakistan Standards Certified
COMPOSITION (NOMINAL)	Pigment: N/A Binder: Alkyd Solvent: Mineral turpentine.
VOLUME SOLIDS	34% (nominal)
FILM THICKNESS/ LITRE/COAT	Wet: 70-80 micrometers Dry: 20-25 micrometers
DRYING TIMES	Single coat at standard film thickness
Touch Dry	3-4 hours
Recoat	16 hours.
PRACTICAL COVERAGE	A guide to the practical coverage which can be achieved under normal conditions is 12-14m ² / litre /coat.
APPLICATION	Brush  Roller  Spray 
THINNING	
Brush Application	For sealing new or bare surfaces thin with up to 0.5 part of Mineral turpentine to 3 parts of paint (15%)

Spray For spray application, add 0.5-0.75 parts of Mineral turpentine to 3 parts of paint (15-25%)

SPRAY RECOMMENDATIONS

Conventional Spray Satisfactory through most equipment

CLEANING UP Clean all equipment with Mineral turpentine immediately after use

SURFACE PREPARATION Surface generally must be clean, dry, free from all defective or poorly adhering material, dirt, and grease, wax etc. previously painted surfaces should be thoroughly rubbed down using a suitable abrasive paper and then dusted off.

SYSTEM INFORMATION

Primer
A thinned first coat of
Dulux Synthetic Clear
Varnish
(F101-0118)

Finish (2-3 coats)
Dulux synthetic clear varnish
(F101-0118)

FLASH POINT 32⁰

SAFETY, HEALTH AND ENVIRONMENT INFORMATION

Flammable. In case of fire use foam, dry powder, AFFF, CO₂ fire extinguisher. Never use water. No smoking. Keep out of reach of children. Keep away from sources of ignition. Keep container tightly closed and upright to prevent leakage when not in use. Work only in areas of good ventilation. Inside always keep doors and windows fully open during application and drying. Irritating to eyes and skin. Contains **COBALT CARBOXYLATE**, May produce an allergic reaction. When applying paint it is advisable to wear eye protection. In case of contact with eyes rinse immediately with plenty of water keeping eyelids apart and seek medical advice. Repeated exposure may cause skin dryness or cracking. Wear gloves while working. In case of contact with skin use soap and water or a recognized skin cleaner. Use suitable respiratory equipment while applying paint in narrow spaces. Dry sanding, flame cutting and or welding of the dry paint film will give rise to dust and or hazardous fumes. Wet sanding should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used. In case of insufficient ventilation during spraying wear suitable respiratory equipment, a suitable cartridge mask should be worn provided the filter is changed regularly. All respiratory equipment must meet an appropriate approved standard. Do not breathe Vapor or sanding dust. If inhalation causes physical discomfort move to fresh air. If discomfort persists or any breathing difficulty occurs, move to fresh air and seek medical advice by showing container label. Harmful if swallowed seek medical advice immediately. Care must be taken when transporting paint. Keep container tightly closed and upright to prevent leakage when not in use. Store in a cool and dry place. In the event of an accident, collect spillage using sand or earth. Do not empty into drains or watercourses. Very toxic to aquatic organisms. May cause long term adverse effects in the aquatic environment. Dispose of any paint waste in accordance with the appropriate environment quality regulations. Safety Data Sheet available for professional users on request. This container is only for paint use

CONTAINS NO ADDED LEAD OR MERCURY