

#### SAFETY HEALTH AND ENVIRONMENTAL INFORMATION:

- Treatments such as sanding, burning off etc. of paint films may generate hazardous dust and/or fumes. Wet sanding/ flatting should be used wherever possible. Work in well ventilated areas. Use suitable personal protection equipment.
- Do not breathe gas / fumes / vapour / spray
- Use only in well ventilated areas
- Keep out of the reach of children
- If swallowed seek medical advice immediately and show this container or label.
- Do not empty into drains.
- Avoid contact with skin or eyes. After contact with skin wash immediately with soap and water or a proprietary skin cleanser. Do not use solvent thinners or white spirits. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- Remove as much paint as possible from brushes and rollers before cleaning.
- Safety data sheet available for professional users on request
- No added Lead, Mercury & Chromium compounds.
- Lead content in dried paint film does not exceed 90 parts per million

#### PRECAUTIONS:

- Keep out of reach of children.
- If medical advice is needed, have product container or label at hand.
- Do not get in eyes, on skin, or on clothing.
- Call a POISON CENTER or doctor/physician if you feel unwell.
- Dispose of contents and container in accordance with all local, regional, national or international regulations.

#### CONTACT US:

Registered office,  
Akzo Nobel India Limited Geetanjali Apartment, 1st floor, 8B Middleton Street, Kolkata 700 071  
In case of any complaints please contact Customer care cell,  
Akzo Nobel India Limited, 9th floor, Magnum Towers, Golf Course Ext Rd, Sector 58, Gurugram -122011,  
Haryana, INDIA.  
Note: The information provided above may change without prior notice.



## PRODUCT DATASHEET

For more details, please visit  
[www.duluxambiance.com](http://www.duluxambiance.com)



## PRODUCT DESCRIPTION:

Dulux Ambiance™ Special Effects Paints include the finest featured finishes and textures to create endless unique combinations to personalise your world.

Dulux Ambiance™ Marble is inspired by the natural beauty of rock, creating the luxurious look of marble finish on your walls.

## PRODUCT FEATURES AND BENEFITS:

### Benefits:

- Ready-to-use, Trowel applied emulsion paint.
- Luxurious Marble/Stone Effect depending on the way of application.
- Optimized rheology and open time for better application.

### Usage:

Ideal for new and previously painted interior masonry, plaster, and building boards surfaces.

### Pack size:

Available only in 1 kg pack (refer to the pack for the fill volume)

### Colour range:

See appropriate Colour Card.

## PHYSICAL FILM PROPERTIES

### Water Resistance:

Resistant to the levels of atmospheric humidity present in normal interior environments. Not suitable for use on immersed surfaces or where there is heavy and prolonged condensation.

## PRODUCT RELATED INFORMATION:

### Composition:

Pigment : Light-fast Non-Lead/Chrome pigment and Mineral Extenders  
Binder : Waterborne Polymer  
Solvent : Water

**Drying Times** : Single coat at standard thickness:

**Touch Dry** : 1-2 hours

**Hard Dry** : 4-8 hours

Drying time may vary according to temperature and humidity.

### Theoretical Coverage:

The spreading capacity of this product will vary considerably according to the roughness and porosity of the surface. On smooth surfaces of average porosity 3 m<sup>2</sup> / kg / coat

### Type Of Finishing:

Marble finish

## APPLICATION RELATED INFORMATION:



### Surface Preparation:

Surfaces must be sound, clean, dry and free from all defective or poorly adhering material, dirt, grease or wax. Remove all loose and defective paint or powdery residues by thorough brushing and scraping, using a stiff fiber brush. Where necessary, wash the surface to remove dirt, grease and powdery or dusty residues. Rinse with clean water and allow to dry. Treat any areas affected mould, lichens, algae and moss with fungicidal treatment. Repair any surface defects with an appropriate filler. Surfaces that remain powdery, friable or chalky after thorough preparation should be sealed with one coat of an appropriate Primer (see below System Recommendation). Where necessary, rub down and then wipe off with a damp, lint free cloth to avoid dust. Do not paint if the wall is saturated with dampness. (Protimeter reading higher than 16%). Allow excess moisture to evaporate.



### Application tools:

Trowel



### Dilution:

Ready to use. No dilution



### Recommended Application Condition:

- Dulux Ambiance™ Marble is recommended for interior walls only.
- Avoid windy conditions in the room.
- Room temperature should ideally be between 20°C and 35°C.
- Very hot, dry conditions are to be avoided.
- Use of any other paint apart from the specially formulated Dulux Ambiance™ Velvet Touch Marble may deviate from the desired finish and make it hard to recondition.

### Prime:

Prime surface with a coat of appropriate Dulux Primer (WBCP/SBCP) first



### Topcoat:

Apply 2 coats of Dulux Ambiance™ Velvet Touch tinted in required colour. Please ensure 3-4 hours drying time between coats.



### Dulux Ambiance™ Velvet Touch Marble:

Apply 3 coats of Dulux Ambiance™ Velvet Touch Marble in required colour with trowel. For the first coat, ensure uniform deposition completely hiding the surface. For the second coat, apply a thin layer of the product in a random manner. For the last coat, apply a very thin layer of the product smoothening it at the same time onto the surface with the blade of the trowel. Buff to attain satin or gloss finish. Sand the surface between the 3 coats with appropriate emery paper. Ensure 4-6 hours drying time between coats. This effect finish is not washable. Please use dry cloth to clean the wall if needed.



### System Recommendation

System Information	Primer/Sealer (1 coat)	Topcoat (3 coats)
Powdery and Alkaline Surfaces	Dulux Primer (SBCP)	
New Surfaces	Dulux Primer (WBCP/SBCP)	Dulux Ambiance™ Velvet Touch Marble
Normal, Sound Surfaces	No Primer required	

### Cleaning Up:

Clean all equipment with clean water immediately after use.

