

## Dulux Woodcare Wood Sealer



<b>Product Code</b>	F016-2221	
<b>Usage</b>	An excellent sealer which penetrates the pores of wood and prevents sink age of topcoat to allow good hold out.	
<b>Packing</b>	0.91 Litre and 3.64 Litres	
<b>Uses</b>	Quality Wooden Furniture	
<b>Composition</b>	Plasticized nitrocellulose	
<b>Other Properties</b>	No Added Lead or Mercury, Pakistan Standards Certified	
<b>Pack</b>	Single pack	
<b>COVERING CAPACITY</b>	11-13m <sup>2</sup> /lit/coat	
<b>FILM THICKNESS</b>	3-5 micrometers/coat	
<b>NUMBER OF COATS</b>	2-3	
<b>DRYING TIME</b>	Surface dry	5 minutes
	Recoat able	10minutes
	Hard dry	2-3 hours
<b>APPLICATION</b>	Conventional spray	
<b>THINNER</b>	Dulux Woodcare Special Thinner	
<b>THINNING</b>	Spray 50-60%	
<b>FLASH POINT</b>	Below 23°C	
<b>COLOUR</b>	Milky	
<b>GLOSS</b>	Slight sheen	

**SURFACE  
PREPARATION  
AND APPLICATION**

Ensure that the wood is dry right through and properly seasoned. Thoroughly scuff with coarse abrasive paper to produce a uniform surface. Level out all the surface rock bottom with manual sanding or by using mechanical sander. Thin down Woodcare Wood Sealer with Dulux Woodcare Special thinner in 1: 1-1.5 ratio. Mix thoroughly and apply 2-3 coats of wood Sealer allowing 10 min. between coats. Allow to dry for 2-3 hours before scuffing and over coating with wood shade or top coat.

**CLEANING UP**

Clean all equipment with Dulux Woodcare Special Thinner immediately after use

**SYSTEM INFORMATION**

New

Dulux Wood sealer (F016-2221) – 2 coats

Finish (3-4 coats)  
Woodcare Lacquer -  
Gloss/Matt (F019)

(Previously painted)

Dulux Wood Sealer (F016-2221) – 2 coats

Dulux PU Lacquer (F-101-8899)

## SAFETY, HEALTH AND ENVIRONMENT INFORMATION

**Highly flammable.** Harmful by inhalation & in contact with skin. Keep out of reach of children. Do not breath solvent Vapor/spray. Keep container in a well-ventilated place. Irritating to eyes, respiratory system & skin. Keep away from food, drink & animal feeding stuff. **Contains Aromatic & Aliphatic solvents.** Wear suitable protective clothing & gloves. Avoid contact with eyes & skin. In case of contact with eyes rinse immediately with plenty of water & seek medical advice. Keep away from sources of ignition. No smoking. Take precautionary measures against static discharges. Wear suitable protective equipment during sanding. Dry sanding of the dry paint film will give rise to paint and wooden dust, such type of surfaces should be sanded with wet sanding paper. If swallowed rinse mouth with water (only if the person is conscious) & show this container or label to a medical practitioner. In case of fire use foam, dry powder, AFFF, CO<sub>2</sub> never use water. Very toxic to aquatic organisms and may cause long term adverse effects in the aquatic environment. Do not empty into drains. Dispose off any paint in accordance with the appropriate Environment Regulations. This container is only for paint use.

Safety Data Sheet available for professional users on request.