


Dulux Aquashield Interior Waterproof Basecoat

USAGE	Dulux Aquashield Interior Waterproof Basecoat is a high-quality premium basecoat that provides waterproof protection to interior walls. Its revolutionary Damp Protect Technology guards interior walls against dampness, enhances top coat life and prevents alkali salt deposits.
Other Properties	Crack proof, Enhances top coat life, Low Odor and Low VOC, No Added Lead or Mercury, Singapore Green Label Certified
PACK SIZE	1 L, 4 L, 16 L
COLOUR RANGE	No color only White
COMPOSTION (nominal)	Pigment: Lightfast Non-Lead/Chrome Pigments Binder: Acrylic Co-Polymer Binder Solvent: Water
VOLUME SOLIDS	White 41% (nominal)
DRYING TIMES	Single coat at standard thickness
Touch Dry	Dependent on temperature and humidity
Recoat	3-4 hours, depends on weather condition.
FILM THICKNESS /LITRE/COAT	DFT: 50-60 micrometers
PRACTICAL COVERAGE:	Varies considerably according to the roughness and porosity of the surface. On smooth surfaces of average porosity, practical coverage 7-9m ² /Liter/coat.
APPLICATION	Brush 
THINNING	No dilution required
CLEANING UP	Clean all equipment with clean water immediately after use
SURFACE PREPARATION	Allow all new surfaces to dry out completely. Remove all loose or defective paint or powdery residues by thorough brushing or scraping using a stiff fiber brush. Treat any areas affected by mould, lichens, algae and moss with Dulux Aquashield Pre-Treatment Coat. Repair minor and major defects in the wall using sand and cement mixture. Allow the surface drying time and prepare the surface as described above

Note: Do not apply Dulux Aquashield Waterproofing Interior Basecoat during wet weather.

SYSTEM INFORMATION

New Surface

Dulux Aquashield Waterproofing Interior Basecoat
1 coat, 2-3 coats of Dulux Acrylic Interior Putty, 1
coat of Dulux Acrylic Interior Primer

Powdery surfaces

Dulux Aquashield Waterproofing Interior Basecoat
1 coat, 2-3 coats of Dulux Acrylic Interior Putty, 1
coat of Dulux Acrylic Interior Primer

Normal, sound surfaces
(Previously painted)

Dulux Aquashield Waterproofing Interior Basecoat
1 coat, 2-3 coats of Dulux Acrylic Interior Putty, 1
coat of Dulux Acrylic Interior Primer

Finish: 3-4
coats of any
interior Dulux
topcoat

SAFETY, HEALTH AND ENVIRONMENT INFORMATION

Treatments such as sanding, burning off etc. of paint films may generate hazardous dust and/or fumes. Wet sanding/ flatting should be used wherever possible. Work in well ventilated areas. Use suitable



personal protection equipment.

Lift with care – gross weight exceeds 10kg

Wear eye/ hand protection. Do not breathe vapors/spray. Use only in well-ventilated areas. Remove as much paints as possible from brushes and rollers before cleaning. Avoid release to the environment. Collect spillage. Keep away from food, drinks and animal feed. Store in a cool and shaded place. Container must be in a secure, upright position and be tightly closed. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. In case of contact with skin wash immediately with soap and water or a proprietary skin cleanser. Do not use solvents or thinners. Do not empty into water course. Safety data sheet available for professional/ user on request.



WARNING

Hazard Statements

May cause an allergic skin reaction. Toxic to aquatic life with long lasting effects.

Precautionary Statements

Keep out of reach of children. If medical advice is needed, have product container or label at hand. Do not get in eyes, on skin, or on clothing. Call a POISON CENTER or doctor if you feel unwell. Dispose of contents and container in accordance with all local, regional, national or international regulations.