



MASTER TEXTURE FINISH

Material Safety Data Sheet

Texture based on acrylic emulsion and selected aggregate marvelous quality. It is 100% acrylic-based and used for all interior/ exterior masonry surfaces such as brick work plaster and cement. A variety of finishes depending on type of roller used and application technique.

Research and Development Department
Master Paint Industries (Pvt.) Ltd.
Phone : 0 4 2 – 111 – 333 – 465,
E-Mail : info@masterpaints.com



WWW.MASTERPAINTS.COM

PRODUCT INFORMATION

Description: Texture based on acrylic emulsion and selected aggregate marvelous quality. It is 100% acrylic-based and used for all interior/ exterior masonry surfaces such as brick work plaster and cement. A variety of finishes depending on type of roller used and application technique.

TECHNICAL INFORMATION:

Color	White
Finish	Matt
Generic Type	Texture Finish
Vol Solid	55 %
Spreading Rate	0.50 kg – 1.50 kg / m ² .
Drying Time	1 -2 hrs at 30 °C.
Recoating Time	2 – 4 hrs.
Thinner / cleaner	Clean water
Weight / Litre	1.60 – 1.75.
Flash Point	None water based
Further coat	Emulsions, alkyd based, P.U or as recommended.
Packing size	6kgs and 24 kgs.

APPLICATION DETAIL :

Roller and hopper gun.

TYPICAL SURFACES :

All loose material including loose plaster, cement splashes, old paint, dust, etc. must be thoroughly removed. New plaster/ concrete must be fully cured. One coat of water based acrylic primer is recommended underneath.

SAFETY AND ENVIRONMENTAL NOTES:

Ensure proper ventilation during application and drying of paint. Avoid inhalation of paint mist and vapours and skin contact. Spillage of paint on skin should immediately be removed with suitable cleanser soap and water. Eyes should be well flushed with water and immediate medical attention should be sought.

Self-Life of product is 03 year (Keep in shade) (Minimum requirement from PSQCA is 02 years).

