



MASTER Water based Cement Primer

Material Safety Data Sheet

Master Wall Primer is high quality wall Sealer for interior and exterior.

Research and Development Department
Master Paints Industries (Pvt) Ltd. 14, Egerton Plaza,
Lahore. Phone : 042-111333465,
info@masterpaints.com

02-Jan-2018





Master Water based Wall Primer (Interior & Exterior)

Material's Technical & Safety Data Sheet

PRODUCT INFORMATION

Description: A high acrylic Water based primer suitable for plastered, masonry, pop lined or preprinted surfaces. It insures a better finish and durability of topcoat. It provides a better adhesion on the surface with excellent inter coat adhesion.

Recommended Use: It is suitable for interior and exterior cements surfaces only.

PHYSICAL CONSTANTS:

Pack Size: 04.00 LTR & 16.00 LTR (Plastic Pack)

Finish: Matt

VOC Content: Less than 50g/LTR

Theoretical Spreading rate : 160/200 Sq.ft/liter/coat

Flash Point : Non.Flash

Color: White

Drying time: 02 -Hours Between coats

Physical constants are subject to normal manufacturing tolerances

APPLICATION DETAIL :

Application Method : Brush, Roller or Spray

Solvent : White

Thinning : By Roller or Spray 30 – 40% & By Brush 60%

No. of Coats : 1 to 2 Coats

Cleaning : Clean all equipment with water

TYPICAL SURFACES:

New Surfaces: Surface must be clean, dry and free from efflorescent salts,

Previously painted surfaces: Thoroughly clean surface Remove all defective or poorly adhering material by rubbing down using a suitable abrasive paper and dust off. Prime with Master wall sealer where needed.,



Use abrasive
paper



Dust off



Seal a coat
with primer

SAFETY :

Keep away from ignition sources because it is flammable. If you are non-professional please don't use large surface. Ventilation should be ensured because it contains white spirit. Always keep container air tight. Please follow all local and national safety regulations.

SAFETY AND ENVIRONMENT NOTES**FIRST-AID MEASURES****GENERAL INFORMATION**

Remove affected person from source of contamination. Get medical attention immediately!

INHALATION

Move injured person into fresh air immediately. Call an ambulance. Be aware that symptoms of lung edema (shortness of breath) may develop up to 24 hours after exposure. Bring these instructions. Place unconscious person on the side in the recovery position and ensure Breathing can take place.

INGESTION

Immediately rinse mouth and drink plenty of water or milk. Keep person under observation. Do not induce vomiting. If vomiting occurs, keep head low. Transport immediately to hospital and take these instructions.

SKIN CONTACT

Remove contaminated clothing immediately and wash skin with soap and water. Consult a physician for specific advice. Burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital.

EYE CONTACT

Immediately flush with plenty of water for up to 15 minutes. Remove any contact lenses and open eyes wide apart. Immediately transport to Hospital or eye specialist.

FIRE-FIGHTING MEASURES**EXTINGUISHING MEDIA**

Use fire-extinguishing media appropriate for surrounding materials.

SPECIAL FIRE FIGHTING PROCEDURES

Beware, risk of formation of toxic and corrosive gases.

SPECIFIC HAZARDS

In case of fire, toxic and corrosive gases may be formed.

PROTECTIVE MEASURES IN FIRE

Leave danger zone immediately.

PERSONAL PRECAUTIONS

Wear protective clothing as described in Section 8 of this safety data sheet. In case of spills, beware of slippery floors and surfaces.

HANDLING AND STORAGE

USAGE PRECAUTIONS

Read and follow manufacturer's recommendations. Always remove grease with soap and water or skin cleaning agent, never use organic solvents. Good personal hygiene is necessary. Wash hands and contaminated areas with water and soap before leaving the work site. Do not eat, drink or smoke when using the product.

STORAGE PRECAUTIONS

Keep away from heat, sparks and open flame. Store in tightly closed original container in a dry, cool and well-ventilated place.

Self-Life of product is 03 year (Keep in shade) (Minimum requirement from PSQCA is 02 years).

STORAGE CLASS

Flammable liquid storage recommended.

===== OTHER INFORMATION
 ===== THE INFORMATION CONTAINED HEREIN IS
 BASED ON DATA BELIEVED TO BE RELIABLE. IT IS TRUE & ACCURATE TO THE BEST
 OF OUR KNOWLEDGE, BUT IS NOT INTENDED TO BE ALL INCLUSIVE. USERS
 SHOULD CONSIDER THIS INFORMATION AS A SUPPLEMENT TO OTHER
 INFORMATION
 GATHERED BY THEM &
 MUST MAKE THEIR OWN DETERMINATION OF SUITABILITY & COMPLETENESS TO
 ASSURE PROPER USE & DISPOSAL.

===== END OF THE REPORT

=====

