



## Wood Master Matt Lacquer

### Material Safety Data Sheet

Wood Master Matt Lacquer is a protective and decorative nitrocellulose based lacquer which provides hard, scratchproof, smooth and transparent matt finish. Formulated as a topcoat on NC paint systems where fast drying, hard and clear high matt finish is required.

**Research and Development Department**  
**Master Paint Industries (Pvt.) Ltd.**  
**Phone : 0 4 2 – 111 – 333 – 465,**  
**E-Mail : [info@masterpaints.com](mailto:info@masterpaints.com)**



*Wood Master Matt Lacquer  
Data Sheet*

## PRODUCT INFORMATION

**Description:** Wood Master Matt Lacquer is a protective and decorative nitrocellulose based lacquer which provides hard, scratchproof, smooth and transparent matt finish. Formulated as a topcoat on NC paint systems where fast drying, hard and clear high matt finish is required.

**Recommended Use:** Suitable for prepared wooden and primed surfaces. Also suitable for industrial lacquer application where fast drying and transparent matt finish is the requirement

### PHYSICAL CONSTANTS:

**Pack Size:** 0.91 LTR ,3.64 LTR & 20.00 LTR (Pack)

**Finish:** Matt

**Color** Clear

**Theoretical Spreading rate :** 120-140Sq.Ft/liter/coat (25±5-microns)  
depending on number of factors

**Drying time:** 15 – 20 min at 30 °C. Recoating time 1 hour.

**Flash Point :** 40 F°

Physical constants are subject to normal manufacturing tolerances

### APPLICATION DETAIL :

**Application Method :** By Spray

**Thinner :** Wood Master Thinner

**Thinning :** Use 1.5 to 2.0 Part of Wood Master Thinner by volume.

**No. of Coats :** 2 Coats

**Typical Painting System:** On Wood

**Cleaning :** Clean all equipment with wood Master thinner.

## TYPICAL SURFACES:

**New Surfaces:** Pre- primed and smooth surface. Ensure that surface is clean, dry and free from grease, oil and other contamination. Wood should be properly sanded and must be scuffed in the direction of wood grains. Seal with Wood Master.

**Previously painted surfaces:** Thoroughly clean surface Remove all defective or poorly adhering material by rubbing down using a suitable abrasive paper and dust off. Seal with Wood Master Sealer,



**Storage** The product must be stored in accordance to national regulations. The product should be kept in well-ventilated place, protected from heat and direct sunlight. The containers must be kept tightly closed.

**Handling** Handle with care. Stir well before use.

## SAFETY AND ENVIRONMENTAL NOTES:

Physical constants are subject to normal manufacturing tolerances. Keep away from ignition sources because it is flammable. If you are Non-professional please don t use large surface. Ventilation should be ensured because it contains white sprit. Always keep container air tight. Please follow all local and national safety regulations.

