



Knifing Filler

Material Safety Data Sheet

Ready mixed high performance oil based filler. This product is recommended for all motor vehicles and wood or metals furniture.

Research and Development Department
Master Paint Industries (Pvt.) Ltd.
Phone : 0 4 2 – 111 – 333 – 465,
E-Mail : info@masterpaints.com



WWW.MASTERPAINTS.COM

PRODUCT INFORMATION

Description: Ready mixed high performance oil based filler. This product is recommended for all motor vehicles and wood or metals furniture.

TECHNICAL INFORMATION:

Colour	Grey
Finish	Matt
Generic Type	Alkyd
Spreading Rate	4 - 8 m ² / L. depending on dft.
Recoating Time	24 hrs.
Thinner / cleaner	White spirit
Weight / Litre	1.6 – 1.75.
Flash Point	34 °C, 93 °F
Further coat	Alkyd based
Packing size	0.91 and 3.64 litres.

APPLICATION DETAIL :

Mask surface and apply filler firmly into place with a putty knife. Fill up slightly higher surface to allow for sanding. Sand after drying on shallow repairs, deep repairs after 2-8 hours. Use medium sand paper; do not continue high speed sanding.

TYPICAL SURFACES :

All loose material including loose paint should be thoroughly removed. Ensure surface is dry, clean and free from contaminants.

SAFETY AND ENVIRONMENTAL NOTES:

Ensure proper ventilation during application and drying of paint. Avoid inhalation of paint mist and vapours and skin contact. Spillage of paint on skin should immediately be removed with suitable cleanser soap and water. Eyes should be well flushed with water and immediate medical attention should be sought.

