



SUPER PRIMER

Material Safety Data Sheet

Super Primer is an acrylic Water based primer suitable for plastered and masonry surfaces. It insures a better finish and durability of topcoat. It provides a better adhesion on the surface with excellent inter coat adhesion.

Research and Development Department
Master Paint Industries (Pvt.) Ltd.
Phone : 0 4 2 – 111 – 333 – 465,
E-Mail : info@masterpaints.com



PRODUCT INFORMATION

Description: Super Primer is an acrylic Water based primer suitable for plastered and masonry surfaces. It insures a better finish and durability of topcoat. It provides a better adhesion on the surface with excellent inter coat adhesion.

TECHNICAL INFORMATION:

Colour	White
Finish	Matt
Generic Type	Interior Primer
Vol Solid	40 % \pm 2
Spreading Rate	16 m ² / L. @25 μ m dft.
Drying Time	1-2 hrs. at 30 °C.
Recoating Time	3 – 4 hrs.
Thinner / cleaner	Clean water
Weight / Litre	1.35 – 1.40.
Flash Point	None
Further coat	Emulsions and alkyd based coatings.
Packing size	03.64 LTR and 14.56 LTR

APPLICATION DETAIL :

Roller, brush, conventional or airless spray.

TYPICAL SURFACES :

All loose material including loose paint should be thoroughly removed. Ensure surface is dry, clean and free from contaminants. New plaster / concrete must be fully cured.

SAFETY AND ENVIRONMENTAL NOTES:

Ensure proper ventilation during application and drying of paint. Avoid inhalation of paint mist and vapours and skin contact. Spillage of paint on skin should immediately be removed with suitable cleanser soap and water. Eyes should be well flushed with water and immediate medical attention should be sought.

