



VARNISH

Material Safety Data Sheet

Alkyd based varnish.

**Research and Development Department
Master Paint Industries (Pvt.) Ltd.**

Phone : 0 4 2 – 111 – 333 – 465,

E-Mail : info@masterpaints.com



PRODUCT INFORMATION

Description: Alkyd based varnish.

TECHNICAL INFORMATION:

Color	Clear pale yellow
Finish	High Gloss
Generic Type	Alkyd
Vol Solid	38 % \pm 2
Spreading Rate	15.2 m ² / L. @25 μ m dft.
Drying Time	3 -5 hrs at 30 °C.
Recoating Time	8 – 12 hrs.
Thinner / cleaner	White spirit
Weight / Litre	0.9 – 1.0 .
Flash Point	34 °C, 93 °F
Further coat	Coat on coat
Packing size	0.91 and 3.64 litres.

APPLICATION DETAIL :

Roller, brush, conventional or airless spray. Thin with good quality white spirit .

TYPICAL SURFACES :

Ensure that surface is clean, dry and free from grease, oil and other contamination. Wood should be properly sanded.

SAFETY AND ENVIRONMENTAL NOTES:

Ensure proper ventilation during application and drying of paint. Avoid inhalation of paint mist and vapours and skin contact. Spillage of paint on skin should immediately be removed with suitable cleanser soap and water. Eyes should be well flushed with water and immediate medical attention should be sought.

